

石化仪器

您可靠的石油化工产品测试合作伙伴

CFR-A5 AUTO 柴油十六烷值测定机


产品介绍

CFR-A5 AUTO 0 100CN 30 85CN

GB/T 386, ASTM D613 IP 41,EN ISO 5165

产品特点

- CFR 82.55mm 114.30mm
- 8:1 36:1 CFR-48
- ASTM D613 GB/T 386 90°



WIFI

技术参数

GB/T 386 ASTM D613 IP 41 EN ISO 5165

0 100 30 85

82.55mm 3.250inch

114.30mm 4.50inch

8:1 36:1

611729.10mm³ 37.33in³

900rpm ± 9rpm

13.0° ± 0.2°

10.30MPa ± 0.34MPa 1500psi ± 50psi

13.0mL/min ± 0.2 mL/min

38 ± 3 100 ± 5

0.20mm ± 0.025mm 0.008in. ± 0.001in.

66 ± 0.5 150 ± 1

100 ± 2 212 ± 3

57 ± 8 135 ± 15

172kPa 207kPa 25psi 30psi

3275kPa ± 138kPa 475psi ± 20psi

-0.25kPa -1.5kPa

635mm ± 25mm 25in. ± 1in.

USB		
LIMS WIFI		
15KW		
15 35 20 90%RH		
AC380V ± 10%,50Hz AC220V ± 10% 50Hz		
1520mm × 850mm × 2000mm		
1200KG		